



beyond standard
solutions

Sittig Technologies GmbH

Goldgewann 4
D-65931 Frankfurt / Main
Germany

Phone:
+49 / 69 / 37 00 02 - 0

Web:
www.sittig.de

E-Mail:
info@sittig.de

PAXModular

IP-Paging Station – NPS05-CTRL02

The IP intercom stations of the PAXModular series are specifically designed for manual announcements – making them ideal for use at airport gates and other high-security environments where audio clarity and ease of use are essential.

Thanks to direct integration into the existing Layer 3 IT network, no dedicated cabling is required. This greatly simplifies installation and reduces infrastructure costs.

Audio signals and control commands are transmitted entirely via IP, ensuring reliable, low-latency, and future-proof communication.

Each key on the intercom station is freely configurable and equipped with RGB backlighting. This allows for clear visual feedback of assigned functions and statuses – such as operational states, priorities, or group control indications.



Network connection	PoE 100M/1G
Protocol Types	UDP, RTP, SSH, TCP/IP
Types of protocols	16 key Buttons with RGB color LED support 1x LED for TALK signalisation 1x LED for Status
Configuration	via. PAXview Server
Voice Coding	16bit PCM uncompressed (48kHz) / RTP
Power supply	Power-Over-Ethernet (PoE),
Connectors	1x RJ45 (Back) 1x 3,5mm Jack BGM Input (mono) (Back)